

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 September 2005 (29.09.2005)

PCT

(10) International Publication Number
WO 2005/090933 A1

(51) International Patent Classification⁷: **G01F 23/38**

(21) International Application Number:
PCT/GB2005/001036

(22) International Filing Date: 18 March 2005 (18.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0406278.2 19 March 2004 (19.03.2004) GB

(71) Applicant (for all designated States except US): **FIRST INERTIA SWITCH LIMITED** [GB/GB]; 2 Columbus Drive, Summit Avenue, Southwood, Farnborough, Hampshire GU14 0NZ (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **THOMAS, Alan,**

Douglas [GB/GB]; 15 Grovelands Road, Spencers Wood, Reading, Berks RG7 1DP (GB). **JOHNSON, Brian** [GB/GB]; 28 Culver Road, Saltash, Devon PL12 4DR (GB).


(74) Agent: **D YOUNG & CO**; 120 Holborn, London EC1N 2DY (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: **FUEL LEVEL SENSOR USING ROTATING ANGLE SENSOR ATTACHED TO FLOAT ON TOTATING ARM**



(57) Abstract: A fuel level sensor having a magnetic position sensor connected to an arm for attachment to a float, wherein the magnetic position sensor comprises a stator and a movable part, the stator having two soft magnetic pieces defining an air gap, which contains a magnetoresistive probe for measuring the variation in induction in the gap, the moveable part comprising a yoke of soft magnetic material displaceable parallel to the magnetic pieces of the stator, and a magnet partly embedded in a cavity in the yoke facing the stator, the poles of the magnet being polarized perpendicularly to direction of movement of the moveable part relative to the stator.



WO 2005/090933 A1



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

— before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*